

NRR

19,500 LBS. GVWR CLASS 5



GVWR/GCWR	19,500/25,500 lbs.
BODY/PAYLOAD ALLOWANCE	12,018-12,997 lbs.
GAWR	
Front	2,275 lbs.
Rear	13,660 lbs.
FRONT AXLE CAPACITY	2,275 lbs.
REAR AXLE CAPACITY	14,550 lbs.
Ratio	5.571
SUSPENSION F/R SPRINGS	Tapered/Multi-Leaf
Capacity	8,440/14,550 lbs.
SERVICE BRAKES	Vacuum/Hydraulic with
Front/Rear	4-Channel ABS Disc Brakes
EXHAUST BRAKE	Standard
TRANSMISSION	Aisin A465id 6-speed auto with double overdrive and lock-up 2 nd -6 th gears
ENGINE	Isuzu 4HK1-TC turbocharged intercooled diesel
Displacement	5.2L (317 in. ³)
Engine Power	215hp @ 2,500 rpm
Engine Torque	452 lb.-ft. @ 1,850 rpm
OIL LEVEL INDICATOR	Dash-mounted oil level check switch and light
ALTERNATOR	140-amp
BATTERIES	2 Maintenance-Free Group 31 750-CCA
TIRES LRR (Low Rolling Resistance)	225/70R19.5F (12-pr) Standard
STEERING	Integral Hydraulic Power
STEERING COLUMN	Tilt and Telescopic
FUEL TANK Standard Optional	30 Gal. in-rail stainless steel 35 Gal. aluminum LH side mount (150 & 176" WB Only) 55 Gal. aluminum LH side mount (176" WB Only)
FUEL TANK	Dual fuel filter with dash mounted indicator light

2023 ISUZU N-SERIES

STANDARD CAB

Wheelbase (in.)	Cab to Axle (in.)	Cab to End of Frame (in.)	Back of Cab (in.)	Overall Length (in.)	Body Length (ft.)
109.0	86.5	129.6	7.7	200.5	10-12
132.5	110.0	153.1	7.7	224.0	12-14
150.0	127.5	170.6	7.7	241.5	16-18
176.0	153.5	196.6	7.7	267.5	18-20
200.0	177.5	220.6	7.7	291.5	22
212.0	189.5	232.6	7.7	303.5	24

CREW CAB

150.0	88.5	131.6	5.3	241.5	12
176.0	114.5	157.6	5.3	267.5	16

